

# Ball valve AT 3591A



## Product information

Fully welded pipe construction with welded end and internal thread. The passage of the ball is restricted by one dimension. Shut-off valve for hot and cold water systems, as well as compressed air and gases. The ball is clamped between two seat rings made of carbon-filled PTFE. All dimensions are equipped with ISO top.



<b>Dimension range (DN)</b>	10 - 50
<b>PN</b>	40
<b>Temperature (°C)</b>	-20 - 204
<b>Main material</b>	Steel

### Area of use

Shut-off valve for hot and cold water systems as well as compressed air and gases.

### Tender text

#### PSB.1 Ball valves

Ball valve AT 3591S with lever, DN ... Housing made of steel with one welded end and one internal threaded connection. With spindle neck adapted for over-insulation. ISO top according to 5211.

### Quality assurance


AFS 2023:5, AFS 2023:5, 8 paragraf, PED 2014/68/EU, PED 2014/68/EU art 4.3

**Product marking:** DN, PS, material in load-bearing parts, manufacturing year and month, and AT number are indicated on the valve's nameplate.

### Energy and environment declaration

**Reach date:** 4/8/2026 3:12:00 PM

**Pos**                      **Component**                      **Material**




## Measurements and weight

Dimension range (DN): 10 - 50

Item number	A	B	C
3591S-010	125	119	
3591S-015	165	119	
3591S-020	175	134	
3591S-025	185	138	
3591S-032	200	142	
3591S-040	220	145	
3591S-050	245	151	

## Function and design

Fully welded pipe construction with welded ends, suitable for direct welding into pipe systems. The passage through the ball is restricted by one dimension. The ball is clamped between two PTFE seat rings. The valve is supplied as standard with an ISO top and a high spindle neck for over-insulation. The upper part of the spindle is always visible and inspectable. The valve has a re-tightenable packing box.



### Technical data

**Main material:** Steel

**Main material code:** Steel P235GH (1.0345)

**Included materials:** Steel, Other

**Included material code:** Steel P235GH (1.0345), PTFE (polytetrafluoroethylene)

**Temperature (°C):** -20 - 204

**PN:** 40

**Connection:** ISO 1127, weld end, Internal thread ISO 228-1 (G, BSPP)

**ETIM classification:** EC011343 - Ball valve

**BK04 code:** 20702 Ball valves

**MagiCAD link:** <https://redir.magicad.cloud/product/0d6e07fa-fd8d-45ec-b421-d102b9826d14>

**Comment to colour:** Blue

**ProductColourAndColourNote:** . Blue

Item number	PN	KVS	Required torque (Nm)	Stem type	Stem measurements	Connection according to ISO 5211	Connection 1 - spec.	Connection 2 - spec.	Leakagerate
3591S-010	40	6	3	Diagonal square	11x11mm	F05	DN10-Dy 17,2mm	3/8	Rate A acc. to EN 12266-1:2012
3591S-015	40	6	3	Diagonal square	11x11mm	F05	DN15-Dy 21,3mm	1/2	Rate A acc. to EN 12266-1:2012
3591S-020	40	15	4	Diagonal square	11x11mm	F05	DN20-Dy 26,9mm	3/4	Rate A acc. to EN 12266-1:2012
3591S-025	40	30	7	Diagonal square	11x11mm	F05	DN25-Dy 33,7mm	1	Rate A acc. to EN 12266-1:2012

Item number	PN	KVS	Required torque (Nm)	Stem type	Stem measurements	Connection according to ISO 5211	Connection 1 - spec.	Connection 2 - spec.	Leakage rate
3591S-032	40	41	16	Diagonal square	11x11mm	F05	DN32-Dy 42,4mm	1 1/4	Rate A acc. to EN 12266-1:2012
3591S-040	40	72	25	Diagonal square	11x11mm	F05	DN40-Dy 48,3mm	1 1/2	Rate A acc. to EN 12266-1:2012
3591S-050	40	104	48	Diagonal square	11x11mm	F07	DN50-Dy 60,3mm	2	Rate A acc. to EN 12266-1:2012

## Installation and maintenance

**Flowdirection:** Bi-directional

**Possible mounting position:** Vertical, Horizontal

The valve can be installed in any position, regardless of the direction of the flow of the medium. Welding should be done with the ball in the fully open position. When gas welding, it is especially important to cool the valve housing at the same time so that the seat rings are not damaged. The valve should be operated regularly to avoid the accumulation of dirt that can lead to leakage.

The company's management system  
is certified by DNV  
ISO 9001 • ISO 14001

# Get into the flow

Get into the flow with Armatec.



**armatec**

info@armatec.se | +46 31 89 01 00 | www.armatec.se