

Ball valve AT 3560-

PRESTERA™



Product information

Ball valve with reduced flow of steel/CPTFE with internal threads and mounting flange for actuator. Suitable for automation. Three-piece for easy service and maintenance. Primarily for steam, gas, hot and cold water.

| | |
|-----------------------------|-----------|
| Dimension range (DN) | 15 - 50 |
| PN | 100 - 125 |
| Temperature (°C) | -28 - 220 |
| Main material | Steel |

Area of use

Shut-off valve primarily for:

- Petroleum products
- Hot and cold water as well as compressed air
- Saturated steam

Tender text

PSB.1 Ball valves

Steel ball valve AT 3560... with reduced flow, internal thread, and steel handle. Packing made of carbon-filled PTFE.

Quality assurance

AFS 2023:5, PED 2014/68/EU

The product is CE marked


Testing is carried out according to ISO 5208. Leakage class A applies to the valve type. The valve is approved according to TA-luft. Material certificate according to EN 10204-3.1 is available.

Product marking: Manufacturer, DN, PN, material code, CE. If applicable, also flow direction. QR code.

Energy and environment declaration

Reach date: 4/15/2026 5:55:00 PM

Pos **Component** **Material**




Measurements and weight

Dimension range (DN): 15 - 50

3560-

| DN | A | B | C | D | F | G | Net weight (kg) |
|----|-----|-------|-----|------|----|------|-----------------|
| 15 | 75 | 76.6 | 140 | 42.6 | 10 | 24.5 | 0.9 |
| 20 | 75 | 76.6 | 140 | 42.6 | 15 | 24.5 | 0.9 |
| 25 | 90 | 81.7 | 140 | 46.8 | 20 | 31.4 | 1.4 |
| 32 | 110 | 98.3 | 170 | 59.3 | 25 | 41.3 | 2.2 |
| 40 | 115 | 101.6 | 170 | 62.6 | 32 | 48.4 | 3.5 |
| 50 | 130 | 128 | 230 | 79 | 32 | 56.3 | 2.9 |



Function and design

Three-piece ball valve for easy service and maintenance.

Homogeneous liquid ball for tight shut-off and low pressure drop.

Self-compensating spindle packing provides a tight valve at high operating frequencies.

Blow-out safe antistatic spindle construction prevents the spindle from being pushed out during pressure surges.

Mounting flange according to ISO 5211 for actuators.

No valve disassembly required for service and installation of actuators.

Valves larger than DN50 have a round valve body/mounting flange.

Technical data

Main material: Steel

Main material code: Steel GP240GH N (1.0619)

Included materials: Stainless steel, Steel, Other

Included material code: Acid resistant stainless steel AISI 316 (1.4401), Steel GP240GH N (1.0619), PTFE (polytetrafluoroethylene), Carbon filled PTFE

Temperature (°C): -28 - 220

PN: 100 - 125

Connection: Internal thread ISO 228-1 (G, BSPP)

ETIM classification: EC011343 - Ball valve

BK04 code: 20702 Ball valves

Comment to colour: Black

ProductColourAndColourNote: . Black

| Item number | KVS | Execution | Connection 1 | Connection 1 - spec. | Connection 2 | Connection 2 - spec. | Connection according to ISO 5211 | Stem measurements |
|-------------|-------|--------------|-------------------------------------|----------------------|-------------------------------------|----------------------|----------------------------------|-------------------|
| 3560-15 | 6.9 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 1/2 | Internal thread ISO 228-1 (G, BSPP) | 1/2 | F03/F04 | 9x9mm |
| 3560-20 | 12.7 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 3/4 | Internal thread ISO 228-1 (G, BSPP) | 3/4 | F03/F04 | 9x9mm |
| 3560-20PK | 12.7 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 3/4 | Internal thread ISO 228-1 (G, BSPP) | 3/4 | F03/F04 | 9x9mm |
| 3560-25 | 29.2 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 1 | Internal thread ISO 228-1 (G, BSPP) | 1 | F03/F04 | 9x9mm |
| 3560-25PK | 29.2 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 1 | Internal thread ISO 228-1 (G, BSPP) | 1 | F03/F04 | 9x9mm |
| 3560-32 | 48.2 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 1 1/4 | Internal thread ISO 228-1 (G, BSPP) | 1 1/4 | F04/F05 | 11x11mm |
| 3560-32PK | 48.2 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 1 1/4 | Internal thread ISO 228-1 (G, BSPP) | 1 1/4 | F04/F05 | 11x11mm |
| 3560-40 | 73.1 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 1 1/2 | Internal thread ISO 228-1 (G, BSPP) | 1 1/2 | F04/F05 | 11x11mm |
| 3560-50 | 107.5 | Reduced bore | Internal thread ISO 228-1 (G, BSPP) | 2 | Internal thread ISO 228-1 (G, BSPP) | 2 | F05/F07 | 14x14mm |

Installation and maintenance

Flowdirection: Bi-directional

Possible mounting position: Vertical, Horizontal

The valve should be regularly exercised to avoid the accumulation of dirt that can lead to leakage.

The company's management system
is certified by DNV
ISO 9001 • ISO 14001

Get into the flow

Get into the flow with Armatec.



armatec

info@armatec.se | +46 31 89 01 00 | www.armatec.se