



Product information

Brass ball valve with drain/fill port, PN 40. Graphite packing. Suitable for use in systems with hot water, cooling water or air.

| | |
|----------------------|---------|
| Dimension range (DN) | 15 - 25 |
| PN | 40 |
| Temperature (°C) | 0 - 150 |
| Main material | Brass |



Area of use

For use in systems with hot water, cooling water or air, where functions of shut-off and venting or draining are desired.
Silicone-free.

PN40 (max 40bar up to 95°C, max 25bar at 150°C)

Free from CE marking for DN≤32 (category according to art. 4.3 directive 2014/68/EU, AFS 2016:1 paragraph 8)

Tender text

PSB.1 Ball valves

Ball valve with full passage and outlet for venting or draining AT 3634, G ... Brass housing, venting device. PN40 (Max 40bar up to 95°C, max 25 bar at 150°C). PTFE packing.

Quality assurance

AFS 2023:5, 8 paragraf

Product marking: Brand and DN.

Energy and environment declaration

Product Bvb: Avoided


Product BVB ID: 92158

Subject to notification under REACH

Reach date: 9/23/2024 11:58:00 AM

| Item number | SCIP number |
|-------------|--------------------------------------|
| 3634-15 | b9c440fa-966d-4c25-a44c-2d1b1239ca91 |
| 3634-20 | b9c440fa-966d-4c25-a44c-2d1b1239ca91 |
| 3634-25 | b9c440fa-966d-4c25-a44c-2d1b1239ca91 |

| Pos | Component | Material |
|-----|-----------|----------|
|-----|-----------|----------|



Measurements and weight

Dimension range (DN): 15 - 25

| DN | A | B | C | Net weight (kg) |
|----|----|----|-------|-----------------|
| 15 | 55 | 53 | 91.5 | 0.301 |
| 20 | 63 | 57 | 91.5 | 0.386 |
| 25 | 73 | 65 | 126.5 | 0.579 |

Function and design

The shut-off valve has full flow capacity. The drain valve is equipped with outlets for venting or draining. AT 3634 is internally threaded.

Technical data

Main material: Brass
Main material code: Brass (CuZn40Pb2) (CW617N) (2.0402)

Included materials: Brass, Steel, Other

Included material code: Brass (CuZn40Pb2) (CW617N) (2.0402)

Material note: Chrome-plated brass.

Temperature (°C): 0 - 150

PN: 40

Connection: Internal thread ISO 228-1 (G, BSPP)

ETIM classification: EC011343 - Ball valve

BK04 code: 20702 Ball valves

Installation and maintenance

Flowdirection: Bi-directional

Possible mounting position: Vertical, Horizontal

See instruction manual. The valve should be operated regularly to avoid the accumulation of dirt that can lead to leakage.

Please feel free to contact us

We answer your questions by e-mail and telephone. No question is too small, no challenge is too big. You are always welcome at Armatec.

info@armatec.se | +46 31 89 01 00 | www.armatec.se

THE COMPANY'S MANAGEMENT SYSTEM
IS CERTIFIED BY DNV
ISO 9001 • ISO 14001