

# Ball valve AT 3606-



## Product information

Ball valve in dezincification-resistant brass with a cast high neck, full bore, internal thread, and steel handle for hot and cold water. Can also be used for vacuum and lighter oils (such as diesel). Graphite packing. 3606 has an extended high neck.



<b>Dimension range (DN)</b>	10 - 50
<b>PN</b>	40
<b>Temperature (°C)</b>	0 - 150
<b>Main material</b>	Brass

### Area of use

Shut-off valve for hot and cold water. Can also be used for air, vacuum, and lighter oils (such as diesel). Silicone-free.

For water, refrigeration, and heating systems (fluid group 2), the temperature range is -0°C to +110°C. Not suitable for drinking water!

For flammable liquids, the maximum pressure is 16 bar.

### Tender text

#### PSB.1 Ball valves

Ball valve in dezincification-resistant brass AT 3606, G... With full passage, internal thread and steel handle. PN 16. Packing in graphite and PTFE-coated ball.

### Quality assurance

AFS 2023:5, 8 paragraf

**Product marking:** Brand and DN.

### Energy and environment declaration

**Product BVB ID:** 8548

**Subject to notification under REACH:** Yes

**Reach date:** 12/06/2026



Item number	SCIP number
3606-10	b9c440fa-966d-4c25-a44c-2d1b1239ca91
3606-15	b9c440fa-966d-4c25-a44c-2d1b1239ca91
3606-20	b9c440fa-966d-4c25-a44c-2d1b1239ca91
3606-25	b9c440fa-966d-4c25-a44c-2d1b1239ca91
3606-32	b9c440fa-966d-4c25-a44c-2d1b1239ca91
3606-40	b9c440fa-966d-4c25-a44c-2d1b1239ca91
3606-50	b9c440fa-966d-4c25-a44c-2d1b1239ca91

## Measurements and weight

**Dimension range (DN):** 10 - 50

## Function and design

AT 3606 has a so-called "blow-out safe" spindle. AT 3606V is equipped with a slow-closing handle. AT 3606 has an aluminum spindle extension mounted.

## Technical data

**Main material:** Brass

**Main material code:** Brass (CuZn36Pb2As) (CW602N)

**Included materials:** Brass, Steel, Other

**Included material code:** Brass (CuZn36Pb2As) (CW602N), PTFE (polytetrafluoroethylene)

**Temperature (°C):** 0 - 150

**PN:** 40

**Connection:** Internal thread ISO 228-1 (G, BSPP)

**ETIM classification:** EC011343 - Ball valve

**BK04 code:** 20702 Ball valves

## Installation and maintenance

**Flowdirection:** Bi-directional

**Possible mounting position:** Vertical, Horizontal

"All valves have internal pipe threads. Tightening of the packing may be necessary for air and gas systems when the test pressure exceeds 6 bar (e). For optimal function, the valve should be operated at least 2 times per year."

The company's management system  
is certified by DNV  
ISO 9001 • ISO 14001

# Get into the flow

Get into the flow with Armatec.



**armatec**

info@armatec.se | +46 31 89 01 00 | www.armatec.se