



Product information

KLINGER® Compensil has excellent sealing properties for all types of applications. It can be used for liquids and gaseous media at low pressures and temperatures and low bolt tension. It also has good resistance to oils, hydrocarbons, refrigerants, and chemicals.

Dimension range (DN)	100 - 250
Temperature (°C)	-100 - 150
Main material	Rubber

---

## Area of use

Primarily used when the rotary valve 231x is mounted in conjunction with loose flange and lower quality welded collar.

## Quality assurance

## Measurements and weight

**Dimension range (DN):** 100 - 250

## Function and design

Mineral fiber bound with NBR, 3A self-releasing surfaces.

## Technical data

**Main material:** Rubber

**Included materials:** Rubber

**Temperature (°C):** -100 - 150

## Installation and maintenance

Ensure that the surfaces of the flanges are clean.

Check that the bolts and flange surfaces are technically sound and free from serious faults.

Always brush in the direction of the thread grooves.

To avoid damage to the flange surface, use a brass mandrel.

### Please feel free to contact us

We answer your questions by e-mail and telephone. No question is too small, no challenge is too big. You are always welcome at Armatec.

[info@armatec.se](mailto:info@armatec.se) | +46 31 89 01 00 | [www.armatec.se](http://www.armatec.se)

THE COMPANY'S MANAGEMENT SYSTEM  
IS CERTIFIED BY DNV  
ISO 9001 • ISO 14001