

# Particle separator AT 8042-



# Product information

Brass particle separator, with particle separator and optional magnetic insert.



<b>Dimension range (DN)</b>	20 - 50
<b>PN</b>	10
<b>Temperature (°C)</b>	0 - 110
<b>Main material</b>	Brass

## Area of use

Exdirt D is effective in separating magnetic, non-magnetic particles, and sludge in heating, cooling, and solar systems where the fluid is water. It can also be installed in systems with mixtures of water/glycols and water/ethanol, but with a maximum concentration of 50%. It is not suitable for systems with mixtures of water/salts.

By applying a particle separator in the system, sludge and particles with a size of up to 5 micrometers (>5micron) are separated, reducing the risk of flow disturbances and circulation problems. It contributes to increased operational reliability under difficult operating conditions and reduces the need for maintenance.

## Tender text

### PMB.22 Separators for the purification of liquid media

Particle separator AT 8042-... made of brass with magnetic insert, PN10, with particle separator and large collection chamber that can be easily drained through a ball valve.

## Quality assurance

AFS 2023:5, 8 paragraph, AFS 2016:1, 8 paragraph, PED 2014/68/EU, PED 2014/68/EU art 4.3

Should not be CE-marked.

**Product marking:** Marked with dimensions, maximum operating pressure, type number, and manufacturer's name.

## Energy and environment declaration

**Product Bvb:** Avoided

**Product BVB ID:** 110738

**Subject to notification under REACH**

**Reach date:** 9/23/2024 11:58:00 AM

## List of details

Pos	Component	Material
1	Separator - mesh	
2	Valve body	Brass
3	Magnetic clip, detachable	
4	Drainvalve with shut-off	

## Measurements and weight

**Dimension range (DN):** 20 - 50

## Function and design

The particle separator effectively removes sludge and particles in heating and cooling systems that are transported with the system fluid. To effectively separate these from the fluid, the separation housing is large in relation to the connection dimension. When the fluid passes through the separator's housing, the flow rate is reduced. This reduces the velocity through the separation housing, allowing dirt and particles to be optimally separated as they pass through a special wire mesh. This allows dirt and particles to be separated from the fluid, fall downwards, and collect at the bottom of the housing. With the help of the magnetic insert, magnetic particles also "stick" to the separator.

Exdirt separates sludge and particles with minimal pressure drop during continuous operation. Accumulated dirt is placed on the bottom of the separator and easily emptied by opening the drain valve, releasing the particles into, for example, a collection bucket without disrupting the system's operation. The sludge accumulation chamber has a large capacity, providing long intervals between flushes.

Dimension range: G 3/4- 2.

## Technical data

**Main material:** Brass

**Included materials:** Brass

**Temperature (°C):** 0 - 110

**PN:** 10

**Connection:** Internal thread ISO 228-1 (G, BSPP), External thread ISO 228-1 (G, BSPP), Olive & Nut

**ETIM classification:** EC010260 - Air-/dirt separator for central heating/cooling system

**Comment to colour:** Brass untreated

## Installation and maintenance

**Possible mounting position:** Horizontal

See product sheet.

The company's management system  
is certified by Kiwa  
ISO 9001 • ISO 14001

# Get into the flow

Get into the flow with Armatec.



**armatec**

post@armatec.no | +47 23 24 55 00 | [www.armatec.no](http://www.armatec.no)