



Product information

Shut-off valve for media with high fiber content or solid particles. With rising or non-rising spindle.

Dimension range (DN)	80 - 1200
PN	6 - 10
Temperature (°C)	0 - 250
Main material	Stainless steel

Area of use

Shut-off valve for media with high fiber content or solid particles.

- Pulp
- Pellets
- Sludge
- Recycled paper
- Powder
- Slurry
- Backwater
- Wastewater

Tender text

PSB.3 Sliding gate valves

Quality assurance

AFS 2023:5, 8 paragraf, PED 2014/68/EU

The product is CE marked

Product marking: Brand, DN, PN, material, flow direction, and seat marking.


Energy and environment declaration

Reach date: 12/3/2024 1:00:10 PM

Reach note: The product is not covered by REACH

List of details


Pos	Component	Material
1	Body	Stainless steel GX5CrNi19-10 (1.4308)
2	Gate	Acid resistant stainless steel AISI 316 (1.4401)
3	Seat	PTFE (polytetrafluoroethylene)
4	Packing	PTFE (polytetrafluoroethylene)



Measurements and weight

Dimension range (DN): 80 - 1200

DN	80	100	125	150	200	250	300	350	400
A	50	50	50	60	60	70	70	96	100
B	92	92	102	102	119	119	119	290	290
C	333	373	406	458	578	679	779	906	1012
D	225	225	225	225	325	325	380	450	450
Net weight (kg)	9	11	13	17	29	40	53	93	126



Function and design

Shut-off valve with handwheel, rising spindle. Full bore provides low pressure drop and minimizes the risk of clogging. Homogeneously cast valve body eliminates leakage to the atmosphere and prevents skewing of the damper. Tight packing box through gland design with PTFE-impregnated braid and extra O-ring. In-house cast guide blocks increase the blade's pressure against the soft seal when closed. Replaceable soft seal and packing box seal.

Technical data

Main material: Stainless steel
Main material code: Stainless steel GX5CrNi19-10 (1.4308)
Included materials: Stainless steel, Other
Included material code: Stainless steel GX5CrNi19-10 (1.4308), Acid resistant stainless steel AISI 316 (1.4401), PTFE (polytetrafluoroethylene)
Temperature (°C): 0 - 250

PN: 6 - 10
Connection: Flanged EN1092
ETIM classification: EC011462 - Knife gate valve
BK04 code: 20709 Slide damper valves
Product colour: RAL 5015 - Sky blue

DN	80	100	125	150	200	250	300	350	400
KVS	496	910	1620	2110	3845	5400	8150	10790	14180

Installation and maintenance

Flowdirection: Uni-directional
Possible mounting position: Vertical
"Mounted between flanges."

Please feel free to contact us

We answer your questions by e-mail and telephone. No question is too small, no challenge is too big. You are always welcome at Armatec.

info@armatec.se | +46 31 89 01 00 | www.armatec.se

THE COMPANY'S MANAGEMENT SYSTEM
IS CERTIFIED BY DNV
ISO 9001 • ISO 14001