



Zertifikat-Nr. der EG-Baumusterprüfung  
Certificate No. of EC Type Approval

Typ Type				Zertifikat-Nr. Certificate No.
Reflex N	18 - 25 Liter	3 bar - 120 °C	04 202 1403 Z 0369/13/D0045	
	35 Liter	3 bar - 120 °C	07 202 1403 Z 0005/2/D0045	
	50 - 140 Liter	6 bar - 120 °C	07 202 1403 Z 0004/2/D0045	
	200 - 1.000 Liter	6 bar - 120 °C	07 202 1403 Z 0600/1/D0045	Rev.1
Reflex NG	18 - 35 Liter	3 bar - 120 °C	07 202 1403 Z 0467/15/D1045	
	50 -140 Liter	3 bar - 120 °C	07 202 1403 Z 0359/13/D0045	
	12 - 140 Liter	6 bar - 120 °C	07 202 1403 Z 0878/15/D1045 Rev.2	
Reflex C	18 - 80 Liter	3 bar - 120 °C	07 202 1403 Z 0437/13/D0045	
Reflex EN/R	18 - 80 Liter	3 bar - 120 °C	07 202 1403 Z 0623/1/D0045 Rev.1 A	
Reflex S	8 - 40 Liter	10 bar - 120 °C	07 202 1403 Z 0617/1/D0045 Rev.2	
	23 Liter	10 bar - 120 °C	07 202 1403 Z 0278/16/D1045	
	50 - 600 Liter	10 bar - 120 °C	07 202 1403 Z 0614/1/D0045 Rev.2	
	35 und 105 Liter	10 bar - 120 °C	07 202 1403 Z 0365/13/D0045 Rev.2	
Reflex SV	18/6 - 50/15 Liter	10 bar - 120 °C	07 202 1403 Z 0057/13/D0045	
Reflex G	100 - 300 Liter	6 bar - 120 °C	07 202 1403 Z 0464/14/D1045 Rev.2	
	1000 – 5000 Liter	6 bar - 120 °C	07 202 1403 Z 0419/2/D0045	
	100 - 500 Liter	10 bar - 120 °C	07 202 1403 Z 1433/14/D1045 Rev.2	
	1000 - 10.000 Liter	10 bar - 120 °C	07 202 1403 Z 0421/2/D0045	
	100 - 300 Liter	16 bar - 120 °C	07 202 1403 Z 0935/14/D1045 Rev.2	
	1.000 - 5000 Liter	16 bar - 120 °C	07 202 1403 Z 0423/2/D0045	
	400 - 5000 Liter	25 bar - 120 °C	07 202 1403 Z 0425/2/D0045 Rev.1	
	80 Liter	40 bar - 215 °C	07 202 1403 Z 0560/14/D1045	

A Auslaufmodell  
Discontinued model