


Ball valve AT 3533- CSF



Product information

Ball valve with full bore, made of steel/PTFE with internal threads and mounting flange for actuator. Suitable for automation. Primarily for gas, steam, hot and cold water.

Dimension range (DN)	15 - 50
PN	63
Temperature (°C)	-29 - 180
Main material	Steel

Area of use

Used for shutting off most liquids and gases found in the process industry, except where stainless material is required.

Tender text

PSB.1 Ball valves

Steel ball valve AT 3533CSF... with full bore, internal thread, and lever in stainless steel.


Quality assurance

AFS 2023:5, AFS 2023:5, 8 paragraph, ATEX 94/9/EG, PED 2014/68/EU

The product is CE marked

Product marking: Brand, DN, PN, material code.

Pos **Component** **Material**



Measurements and weight

Dimension range (DN): 15 - 50

DN	A	B	C	D	Net weight (kg)
15	75	0	70.9	110	0.6
20	80	0	73.4	110	0.8
25	90	0	84.1	135	1.3
32	110	0	89.3	135	1.9
40	120	0	109.5	165	3
50	140	0	118.9	165	4.5

Function and design

Quality valve, cast in steel with fire-safe design and lockable handle. Three-piece construction. Blow-out proof antistatic spindle construction prevents the spindle from being pushed out during pressure surges. Mounting flange according to ISO 5211 for actuators. No valve disassembly required for service and installation of actuators. Valves larger than DN50 have a round valve body/mounting flange.

Technical data

Main material: Steel

Included materials: Stainless steel, Steel, Other

Included material code: Stainless steel AISI 304 (1.4301), Acid resistant stainless steel AISI 316 (1.4401), Steel GP240GH N (1.0619), Carbon filled PTFE

Temperature (°C): -29 - 180

PN: 63

Connection: Internal thread ISO 228-1 (G, BSPP)

ETIM classification: EC011343 - Ball valve

BK04 code: 20702 Ball valves

Installation and maintenance

Flowdirection: Bi-directional

Possible mounting position: Vertical, Horizontal

No disassembly or gasket replacement in connection with welding. The ball valve should be exercised regularly.

The company's management system
is certified by DNV
ISO 9001 • ISO 14001

Get into the flow

Get into the flow with Armatec.



armatec

info@armatec.se | +46 31 89 01 00 | www.armatec.se