


# Knife Gate Valve AT 2205-



## Product information

Shut-off valve for media with high fiber content or solid particles. With rising or non-rising spindle.

|                             |                 |
|-----------------------------|-----------------|
| <b>Dimension range (DN)</b> | 50 - 1200       |
| <b>PN</b>                   | 6 - 10          |
| <b>Temperature (°C)</b>     | 0 - 120         |
| <b>Main material</b>        | Stainless steel |

### Area of use

Shut-off valve for media with high fiber content or solid particles.

- Pulp
- Pellets
- Sludge
- Recycled paper
- Powder
- Slurry
- Backwater
- Wastewater

### Tender text

**PSB.3 Sliding gate valves**

### Quality assurance

AFS 2023:5, 8 paragraf, PED 2014/68/EU art 4.3

**The product is CE marked**

**Product marking:** Brand, DN, PN, material, flow direction, and seat marking.


### Energy and environment declaration

**Reach date:** 12/3/2024 1:00:09 PM

**Reach note:** The product is not covered by REACH

## List of details


| Pos | Component | Material   |
|-----|-----------|--|
| 1   | Body      | Stainless steel GX5CrNi19-10 (1.4308)            |
| 2   | Gate      | Acid resistant stainless steel AISI 316 (1.4401) |
| 3   | Seat      | EPDM (ethylene propylene diene monomer rubber)   |
| 4   | Packing   | PTFE (polytetrafluoroethylene)                   |



## Measurements and weight

**Dimension range (DN):** 50 - 1200

| DN              | 80  | 100 | 150 | 200 | 250  | 350  | 400  |
|-----------------|-----|-----|-----|-----|------|------|------|
| A               | 50  | 50  | 60  | 60  | 70   | 70   | 100  |
| B               | 92  | 92  | 102 | 119 | 119  | 119  | 290  |
| C               | 333 | 373 | 458 | 578 | 679  | 679  | 1012 |
| D               | 469 | 502 | 644 | 815 | 1016 | 1016 | 1442 |
| E               | 225 | 225 | 225 | 325 | 325  | 325  | 450  |
| Net weight (kg) | 9   | 11  | 17  | 28  | 40   | 40   | 116  |



## Function and design

Shut-off valve with handwheel, rising spindle. Full bore provides low pressure drop and minimizes the risk of clogging. Homogeneously cast valve body eliminates leakage to the atmosphere and prevents skewing of the damper. Tight packing box through gland design with PTFE-impregnated braid and extra O-ring. In-house cast guide blocks increase the blade's pressure against the soft seal when closed. Replaceable soft seal and packing box seal.

## Technical data

**Main material:** Stainless steel

**Main material code:** Stainless steel GX5CrNi19-10 (1.4308)

**Included materials:** Stainless steel, Rubber, Other

**Included material code:** Stainless steel GX5CrNi19-10 (1.4308), Acid resistant stainless steel AISI 316 (1.4401), EPDM (ethylene propylene diene monomer rubber), PTFE (polytetrafluoroethylene)

**Temperature (°C):** 0 - 120

**PN:** 6 - 10

**Connection:** Flanged EN1092

**ETIM classification:** EC011462 - Knife gate valve

**BK04 code:** 20709 Slide damper valves

**Product colour:** RAL 5015 - Sky blue

| DN  | 80  | 100 | 150  | 200  | 250  | 350   | 400   |
|-----|-----|-----|------|------|------|-------|-------|
| KVS | 496 | 910 | 2110 | 3845 | 5400 | 10790 | 14180 |

## Installation and maintenance

**Flowdirection:** Uni-directional

**Possible mounting position:** Vertical

"Mounted between flanges."

The company's management system  
is certified by DNV  
ISO 9001 • ISO 14001

# Get into the flow

Get into the flow with Armatec.



**armatec**

info@armatec.se | +46 31 89 01 00 | www.armatec.se