


Knife Gate Valve AT 2201-



Product information

Shut-off valve for media with high fiber content or solid particles. With rising or non-rising spindle.

Dimension range (DN)	50 - 1200
PN	6 - 10
Temperature (°C)	0 - 120
Main material	Cast iron

Area of use

Shut-off valve for media with high fiber content or solid particles. - Pulp - Pellets - Sludge - Recycled paper - Powder - Slurry - Backwater - Wastewater.

Tender text

PSB.3 Sliding gate valves

Quality assurance

AFS 2023:5, 8 paragraf, PED 2014/68/EU art 4.3

The product is CE marked

Product marking: Brand, DN, PN, material, flow direction, and seat marking.


Energy and environment declaration

Reach date: 12/3/2024 1:00:06 PM

Reach note: The product is not covered by REACH

List of details


Pos	Component	Material
1	Body	Cast iron GJL-250 (GG25)
2	Gate	Stainless steel AISI 304 (1.4301)
3	Seat	EPDM (ethylene propylene diene monomer rubber)
4	Packing	PTFE (polytetrafluoroethylene)



Measurements and weight

Dimension range (DN): 50 - 1200

DN	100
A	50
B	92
C	373
D	502
E	225
Net weight (kg)	11



Function and design

Shut-off valve with handwheel, rising spindle. Full bore provides low pressure drop and minimizes the risk of clogging. Homogeneously cast valve body eliminates leakage to the atmosphere and prevents skewing of the damper. Tight packing box through gland design with PTFE-impregnated braid and extra O-ring. In-house cast guide blocks increase the blade's pressure against the soft seal when closed. Replaceable soft seal and packing box seal.

Technical data

Main material: Cast iron

Main material code: Cast iron GJL-250 (GG25)

Included materials: Cast iron, Stainless steel, Rubber, Other

Included material code: Stainless steel AISI 304 (1.4301), Cast iron GJL-250 (GG25), EPDM (ethylene propylene diene monomer rubber), PTFE (polytetrafluoroethylene)

Temperature (°C): 0 - 120

PN: 6 - 10

Connection: Flanged EN1092

ETIM classification: EC011462 - Knife gate valve

BK04 code: 20709 Slide damper valves

Product colour: RAL 5015 - Sky blue

Installation and maintenance

Flowdirection: Uni-directional

Possible mounting position: Vertical

"Mounted between flanges."

The company's management system
is certified by DNV
ISO 9001 • ISO 14001

Get into the flow

Get into the flow with Armatec.



armatec

info@armatec.se | +46 31 89 01 00 | www.armatec.se